


SANUTAL

www.sanutal.be

WP Monobloc flexibel 6Kw en 10Kw
Flexible pour PAC Monobloc 6Kw et 10Kw



Omschrijving / Description	Artikelcode / Code d'article
Koppeling / Raccord DN25 M	17.25.1
Koppeling / Raccord DN25 F	17.25.0
Koppeling Raccord DN32 M	17.32.1
Koppeling / Raccord DN32 F	17.32.0
Buizensnijder / Coupe tube	15.RS-6645-2
Isolatie tape / Tape isolation	99.ATAPE

Design I DIN 1,4404-AISI316 L
+ iso 13mm + PVC cover

Artikelcode Code d'article	Omschrijving Description	Afmetingen Dimensions		Werkdruk Pression de service		barstdruk D'éclatement		Buigradius Rayon de courbure	
		D1 mm	D2 mm	Bar	bij/à 20°C	Bar	Déclatement	Eénmalige Statique	Dynamisch Dynamique
17.25.05	Flexibel inox + iso Monobloc DN25 X 5Meter	25,6	31,7	15	15	85	35	260	260
17.25.10	Flexibel inox + iso Monobloc DN25 X 10Meter	25,6	31,7	15	15	85	35	260	260
17.25.15	Flexibel inox + iso Monobloc DN25 X 15Meter	25,6	31,7	15	15	85	35	260	260
17.25.25	Flexibel inox + iso Monobloc DN25 X 25Meter	25,6	31,7	15	15	85	35	260	260
17.25.50	Flexibel inox + iso Monobloc DN25 X 50Meter	25,6	31,7	15	15	85	35	260	260
17.32.05	Flexibel inox + iso Monobloc DN32 X 5Meter	34,6	41,1	12	12	85	40	300	300
17.32.10	Flexibel inox + iso Monobloc DN32 X 10Meter	34,6	41,1	12	12	85	40	300	300
17.32.15	Flexibel inox + iso Monobloc DN32 X 15Meter	34,6	41,1	12	12	85	40	300	300
17.32.25	Flexibel inox + iso Monobloc DN32 X 25Meter	34,6	41,1	12	12	85	40	300	300
17.32.50	Flexibel inox + iso Monobloc DN32 X 50Meter	34,6	41,1	12	12	85	40	300	300